



ALADINO

code 1900/1910

Specifications

Aladino switch

Plug-in cable **Code 1900 jack**

Without cable and connector (to be ordered separately).

Switch On-Off .

Weight 246 gr.



Aladino switch

Fixed cable **Cod. 1900 fix**

Switch On-Off.

Weight 246 gr. without cable



Aladino dimmer

Plug-in cable **Cod. 1910 jack**

Without cable and connector (to be ordered separately).

Supplied with built-in DIMMER 0% - 100% .

Switch is separated from the dimmer

Weight 282 gr.



Aladino dimmer

Fixed cable **Cod. 1910 fix**

Supplied with built-in DIMMER 0% - 100% .

Switch is separated from the dimmer

Weight 282 gr. without cable



Specifications dimmer:

Input voltage 6-16VCC max 8.5A.

Operating frequency 25KHZ.

Protection against polarity reverse.

For halogen mirrored dichroic lamps 20W, 35W, 50W (3150°K).

Aluminium housing: the body is designed as a radiator in order to ensure an excellent cooling.

The yoke is fixed to the body by self-blocking screws, and it is provided with universal camera mount (male shoe or 1/4" threaded screw).

Cables and connectors options for Aladino "jack":

Code 1917: CABLE ALADDIN/BATTERIES 150cm XLR4

Code 1918: CABLE ALADDIN/BATTERIES 60cm XLR4

Code 1919: CABLE ALADDIN/BATTERIES 25cm POWER TAP ANTON BAUER- SONY D-mount

Code 1920: CABLE ALADDIN/BATTERIES 60cm POWER TAP ANTON BAUER

Code 1921: CABLE ALADDIN/BATTERIES 60cm BP 90 PAG

Code 1922: CABLE ALADDIN/MAINS WITH TRANSFORMER DIMMER 12V/220V

Code 1927: CABLE ALADDIN/ BATTERIES 150cm JACK 2.1mm with locking screw.



Accessories

Diffuser (frosted) glass integral to the fixture.

- Code 1901:** 2- leaf barndoor with integral flip up/down dichroic 5600°k filter.
- Code 1902:** 2- leaf barndoor with integral flip up/down dichroic 5600°k filter + extra diffuser glass.
- Code 1903:** 3- leaf barndoor
- Code 1904:** Female spigot 16mm 5/8"
- Code 1905:** Spigot lift-up 4 cm.
- Code 1906:** Spigot lift-up 8 cm.
- Code 1907:** Sliding bracket 6 cm.
- Code 1908:** Sliding bracket 10 cm.
- Code 1909:** Camera handle clamp.
- Code 1911:** Handle (with 1904 included)
- Code 1912:** Sony thread locking shoe
- Code 1924:** POCKET BATTERY 12V NiMH 4.1Ah
- Code 1925:** QUICK CHARGER 12V FOR BATTERY 1924 NiMH

Photometrics

ALADINO DICROIC

LAMP TYPE 50W 12V IRC 38°	DISTANCE 1m	Lx 1590
LAMP TYPE 35W 12V IRC 38°	DISTANCE 1m	Lx 900
LAMP TYPE 20W 12V IRC 24°	DISTANCE 1m	Lx 870





ALADINO

POWER SYSTEM

Pocket battery 12V Ni-Mh Code 1924

Specifications

Type: 10 NiMH cells in hard case with adjustable belt
 Volts: 1,2V per cell
 Nominal capacity: 4100mAh
 Max discharge range: from 410mA to 12300mA
 Cycles: 500 cycles (Standard IEC)
 Weight: 720 gr.
 Measures: height 155mm, length 75mm, width 42mm



LAMP	DURATION	CONSUMPTION
20W	2h20'	1.6A
35W	1h25'	2.9A
50W	1h00'	4.1A

charging time with charger 1925: 5 hours

Quick charger Code 1925

Quick charger for Pocket Battery ref. 1924



Specifications

Type: switching - 90-264V AC/50 - 60Hz
 Providing protection against overheating and overcharging.
 It can charge 10-12 Ni-CD or NiMH cells from 12V to 14V
 Weight: 286 gr.

