

# BLONDE MO/PO



code 1610/220

## Specifications

### Compactbeam 1610 P.O.

2000W 120/240V yoke mount kg. 3,870

### Varibeam 220 M.O.

2000W 120/240V yoke mount kg. 3,070

Lightweight construction: code 1610 aluminum housing; code 220 steel housing  
Epoxy anti-scratch finish on outside: standard colour blonde, black on request  
Heat resistant matt black finish on the inside  
Extra-pure aluminum reflector, diffusing finish on models 1610  
Pole operated spot-flood control on model 1610, manual spot-flood on model 220  
Aluminum yoke mount with 5/8" (16 mm.) socket  
Power cable 3,20 m. long. Section 3x2,5 mm<sup>2</sup>. CEI 20-35 Flame retardant, Fire resistant  
In-line switch 10Amp 250V (20Amp. 125V), with housing.

## Accessories

For model 1610 only:

**Code 1612:** 1,076 gr. Four leaf barndoor with gel clips.

For model 220 only:

**Code 226:** 296 gr. Wire guard with accessories holder ring.

**Code 221:** 886 gr. Four leaf barndoor with gel clips.

**Code 227:** 980 gr. Four leaf barndoor/wire guard assembly with gel clips.

**Code 222:** 545 gr. Accessory holder.

Other accessories for Blondes 1610 or accessory holder 222:

**Code 228:** 90 gr. Wire guard.

**Code 231:** 460 gr. Safety glass.

**Code 223:** 460 gr. Dichroic daylight filter.

**Code 225:** 110 gr. Single scrim.

**Code 224:** 160 gr. Double scrim.

**Code 230:** 90 gr. Half single scrim.

**Code 229:** 110 gr. Half double scrim.

**Code 236:** Master stand (master 004) alu

**Code 302:** Mini stand (ranker 005MT) steel

**Code 303:** Maxi stand (master 004MT) steel

**Code 338:** Crocodile large clamp with 5/8" (16mm) spigot.

## Photometrics

	code 1610		code 220	
	SPOT	FLOOD	SPOT	FLOOD
DISTANCE 3 m (2000w)				
light center value	3984	948	3250	1646
beam angle= beam at 50% peak value	31°	80°	36°	56°
field angle= beam at 10% peak value	74°	107°	74°	96°
RATIO	1:4.2		1:1.97	

Fitting halogen lamps RX7s type FEX 3200°K



CODE 1610



CODE 220