

# PHOTOFLOOD/MINIPINZA



code 115/100

## Specifications

### Photoflood 115 500W - 120/240V

Clamp + jointed arm mount

kg. 1,170

### Minipinza 100 250W - 120/240V

Clamp + jointed arm mount

kg. 1,140

Aluminum housing

Epoxy anti-scratch red finish: black and silver colour on request

Aluminium finish on the inside

Lampholder E 27

Protective lampholder housing in fibre glass

Black fibre glass clamp with flexible arm

Power cable 3,50 m. long, section 3x1,5 mmq CEI 20-35 Flame retardant, Fire resistant

In-line switch 8Amp 250V (16Amp 125V)

### For architectural applications

fitting long life halogen lamps type E27 250w type 64480



## Accessories

### Photoflood:

**Code 802:** 380 gr. Four leaf barndoor with gel clips.

**Code 801:** 435 gr. Four leaf barndoor/wire guard assembly with gel clips.

**Code 807:** 290 gr. Snoot  $\varnothing$  85 mm - 245mm long

**Code 806:** 240 gr. Snoot  $\varnothing$  134 mm - 132mm long

### Minipinza:

**Code 159:** 215 gr. Four leaf barndoor with gel clips.  
(It can fit the accessories line of Lilliput.)

## Photometrics

DISTANCE 3 m (500w - argaphoto PF318)	
light center value	302
beam angle= beam at 50% peak value	98°
field angle= beam at 10% peak value	137°

Fitting incandescent and fluorescent lamps with E27 base

